




PRECISOR® II Pneumatic and Electro-Pneumatic Positioner

Rotary Operation, Field Selectable Cam Design, 316 SS Models



Proximity Series 265 PRECISOR® II Pneumatic and Electro-Pneumatic Positioners combine outstanding performance with an extremely low price, making it an exceptional value for industrial applications. Rotary valves with single or double acting pneumatic actuators can be precisely controlled, such as our ball and butterfly valves. The PRECISOR® II positioner proportionally modulates the valve from either an electric 4 to 20 mA or pneumatic 3 to 15 psig input signal, based on the model chosen and is user-selectable for single or double action. Its rugged, durable design makes it ideal for use in harsh environments, while maintaining precise, accurate positioning of the control elements. Includes a bracket for mounting onto actuators with NAMUR standard connections, and features a versatile linear cam for direct action, reverse action, or split ranges.

FEATURES

- Field selectable cam for direct or reverse acting
- User selectable single or double action.

Model	Input	Lever Type	Enclosure
265NR-D5	3 to 15 psig	NAMUR	Aluminum
265ER-D5	4 to 20 mA	NAMUR	Aluminum
265ER-D5SS	4 to 20 mA	NAMUR	Stainless Steel

SPECIFICATIONS

- Input Signal:** Pneumatic: 3 to 15 psig (0.2 to 1 bar); Electro-pneumatic: 4 to 20 mA DC.
- Input Impedance:** (265ER only): 250 ±15 Ω.
- Enclosure Material:** Aluminum diecasting or 316 SS.
- Air Supply:** 20 to 101 psig (1.4 to 7.0 bar).
- Air Supply Connection:** 1/4" NPT.
- Gage Connection:** 1/8" NPT.
- Electrical Connection:** Screw terminal.
- Conduit Connection:** 1/2" NPT (265ER only).
- Linearity:** ±2% FS.
- Hysteresis:** 1% FS.
- Sensitivity:** ±0.5% FS.
- Repeatability:** ±0.5% FS.
- Air Consumption:** 0.10 scfm (3 LPM) at 20 psig (1.4 bar) supply.
- Flow Capacity:** 28 scfm (80 LPM) at 20 psig (1.4 bar) supply.
- Stroke:** 0 to 90°.
- Enclosure Rating:** IP66 (NEMA 4X).
- Temperature Limits:** Aluminum: -4 to 158°F (-20 to 70°C); SS: -40 to 158°F (-40 to 70°C).
- Weight:** 265NR: 3.1 lb (1.7 kg); 265ER: 6.2 lb (2.8 kg).
- Agency Approvals:** CE (265ER only).

Pneumatic Hosing and Fittings

Hosing and fittings for connecting positioners, current to pressure transducers, air filter gauges and other accessories to pneumatic actuated valves.

Model	Description
A-228	SS steel flex hose, 12" (30.48 cm) L, 1/8" male NPT connections
A-332	Brass adapter, 1/8" female NPT to 1/4" male NPT



VALVES

Positioners