

Model DKT-1

Pocket-Size Thermocouple Thermometer

Selectable °F/°C, Accepts Mini-Plug Input

51/64 [20.24]



The Model DKT-1 Pocket-Size Thermocouple Thermometer accurately monitors temperatures in a variety of applications. The wide measurement range and selectable engineering units allow users to easily view readings in either °F or °C. The automatic power down feature conserves battery life. This compact thermometer accepts any K-type thermocouple sensors (sold separately) with mini-plug connectors.

Model DKT-1, Thermocouple Thermometer

ACCESSORIES

1818-0074, Immersion Probe 1818-0078. Penetration Probe 1818-0082. Surface Probe 1818-0085. Air Duct Probe

SPECIFICATIONS

Measurement Range: -83.2 to 1999°F (-64 to 1400°C). Operating Temperature: 32 to 122°F (0 to 50°C). Accuracy: ± 1% of reading or 1.8°F (1.0°C).

°C/°F

1-45/64

[43.26]

Probe Connection: K type mini-jack. Resolution: 0.1°F/°C.

Power Requirements: 3 V CR2032 lithium metal battery, installed functional, user

3-5/64

[78.18]

replaceable.

Battery Life: Estimated 100 hours continuous use.

Weight: 1.42 oz (40.15 q). Agency Approvals: CE.

OPTION

For NIST traceable calibration certificate, use order code NISTCAL-TG.

Thermometers, Thermocouple